

COMPLETE VEHICLE EU CERTIFICATE OF CONFORMITY

The undersigned, Mr. Luo Gen / Director
Hereby certifies that the following complete vehicle:

- 0.1. Make (trade name of the manufacturer): **LUQI**
- 0.2. Type: HL5.0S (CV * Type): N.A.
- 0.2.1. Variant: 0 (CV * Variant): N.A.
- 0.2.2. Version: 0 (CV * Version): N.A.
- 0.2.3. Commercial name (if available): HL5.0S
(CV * Commercial name (if available)): N.A.
- 0.3. Category, subcategory and sub-subcategory of vehicle: L3e-A1
(CV * Category, subcategory and sub-subcategory of vehicle): N.A.
- 0.4. Company name and address of manufacturer:
LUQI INTELLGENT TECHNOLOGY CO., LTD
95 High Street Office B Great Missenden HP16 0AL United Kingdom
- 0.4.2. Name and address of manufacturer's authorised representative (if any):
GreenKar Automotive S.r.l.
Via di Quarto Peperino, 22 CAP 00188 - Roma, Italy
- 0.5.1. Location of the manufacturer's statutory plate(s): R: x1090, y280, z370
- 0.5.2. Method of attachment of the manufacturer's statutory plate(s): By riveted
- 0.6. Location of the vehicle identification number: R: x490, y320, z580
1. Vehicle identification number: ☆SLJF00008N1000024☆

conforms in all respects to the type described in EU type-approval e9*168/2013*11708*00 (type-approval number including extension number) (CV* type-approval number including extension number) issued on 15,12,2020 (date of issue) (CV* date of issue) and can be permanently registered in Member States having right/left-hand traffic and using metric/imperial units for the speedometer.

Great Missenden, United Kingdom

(place)



(signature)

16,11,2022

(date)

General construction characteristics

- 1.3. Number of axles: 2 and wheels: 2
- 1.3.1. Axles with twinned wheels: N.A.
- 1.3.2. Powered axles: R
- 6.2.4. Advanced braking system: ABS / CBS / Both ABS and CBS / None

Main dimensions

- 2.2.1. Length: 2150 mm
- 2.2.2. Width: 940 mm
- 2.2.3. Height: 1150 mm
- 2.2.4. Wheelbase: 1530 mm
- 2.2.4.1. Wheelbase sidecar: N.A.
- 2.2.5. Track width: N.A.
- 2.2.5.1. Track width front: N.A.
- 2.2.5.2. Track width rear: N.A.
- 2.2.5.3. Track width sidecar: N.A.
- 2.2.10.6. Ground clearance between the axles: N.A.
- 2.2.15. Wheelbase to ground clearance ratio: N.A.
- 2.2.17. Seat height: N.A.

Masses

- 2.1.1. Mass in running order: 103 kg
- 2.1.2. Actual mass: 198 kg
- 2.1.3. Technically permissible maximum laden mass: 293 kg
- 2.1.3.1. Technically permissible maximum mass on front axle: 93 kg
- 2.1.3.2. Technically permissible maximum mass on rear axle: 200 kg
- 2.1.3.3. Technically permissible maximum mass on sidecar axle: N.A.
- 2.1.7. Technically permissible maximum towable mass:
Braked: N.A. Unbraked: N.A.
- 2.1.7.1. Technically permissible maximum laden mass of the combination: N.A.
- 2.1.7.2. Technically permissible maximum mass at the coupling point: N.A.

Powertrain

- 3.1.1.1. Manufacturer: N.A.
- 3.1.1.2. Engine code (as marked on the engine or other means of identification): N.A.
- 3.2.1.2. Working principle of the combustion engine: ~~internal combustion engine (ICE)~~ / positive ignition / ~~compression ignition~~ / external combustion engine (ECE) turbine / compressed air
- 3.2.1.4.1. Number of cylinders: N.A.
- 3.2.1.4.2. Arrangement of cylinders: H/V/O/S
- 3.2.1.5. Engine capacity: N.A.
- 1.9. Maximum net power:
N.A. (CV*: N.A.)
- 1.10. Ratio maximum net power/mass of the vehicle in running order:
N.A. (CV*: N.A.)
- 3.2.3.1. Fuel type: N.A.
- 3.2.3.2. Vehicle fuel combination: mono-fuel/bi-fuel/flex-fuel
- 3.2.3.2.1. Maximum amount of bio-fuel acceptable in fuel: N.A.

3.1.2.1. Manufacturer: Taizhou Quanshun E-Drive Technology Co., Ltd.
3.1.2.2. Electric motor code (as marked on the engine or other means of identification):

60VC40SQS01.124

3.3.3.4. 15/30 minutes power: 4.0 kW

3.1.3.1. Manufacturer: N.A.

3.1.3.2. Application code (as marked on the engine or other means of identification): N.A.

3.3.1. Electric vehicle configuration: pure electric/hybrid electric/manpower electric

3.3.5.2. Category of hybrid electric vehicle: ~~off-vehicle charging/not off-vehicle charging~~

3.9.2. Maximum assistance factor: N.A.

Maximum speed

1.8. Maximum speed of vehicle: 80 km/h (CV*: N.A.)

3.9.3. Maximum vehicle speed for which the electric motor gives assistance: N.A.

Drive-train and control

3.5.3.9. Transmission (type): W

3.5.4. Gear ratios: 1

3.5.4.1. Final drive ratio: 1

3.5.4.2. Overall gear ratio in highest gear: N.A.

Installation of tyres

6.18.1.1. Tyre size designation:

Axle 1: 140/70-17 M/C Axle 2: 215/40-13 M/C

Minimum Load capacity index:

Axle 1: 26 Axle 2: 52

Minimum speed category symbol:

Axle 1: F Axle 2: F

Recommended pressure:

Axle 1: 250 kpa Axle 2: 150 kpa

Rim size:

Axle 1: J17*4.5 Axle 2: J13*7.0

Sidecar wheel: N.A.

Bodywork

6.20.2.1. Door configuration and number of doors: N.A.

6.16.1. Number of seating positions: 2

6.16.1.1. Location and arrangement: N.A.

Coupling devices

7.2.8. Type-approval number of coupling-device: N.A.

Environmental performance

4.0.1. Environmental step: Euro 5

4.0.6. Sound level measured according to: N.A.

4.0.6.1. Stationary: N.A. dB(A) (CV*: N.A.)

4.0.6.2. Drive-by: N.A. dB(A) (CV*: N.A.)

4.0.6.3. Limit value for L_{urban} : N.A. dB(A) (CV*: N.A.)

3.2.15. Exhaust emissions measured according to N.A.

3.2.15.1. Type I test: tailpipe emissions after cold start, including the deterioration factor, if applicable:

CO: N.A. mg/km (CV*: N.A.)

THC: N.A. mg/km (CV*: N.A.)

NMHC: N.A. (CV*: N.A.)

NOx: N.A. mg/km (CV*: N.A.)

HC+NOx: N.A. (CV*: N.A.)

PM: N.A. (CV*: N.A.)

3.2.15.2. Type II test: tailpipe emissions at (increased) idle and free acceleration:

HC: N.A. ppm at normal idling speed and: N.A. ppm at high idle speed (CV*: N.A.)

CO: N.A. %vol at normal idling speed and: N.A. %vol at high idle speed (CV*: N.A.)

3.2.15.3. Smoke corrected absorption coefficient: N.A. (CV*: N.A.)

Energy efficiency

4.0.2. Fuel consumption: N.A. (CV*: N.A.)

4.0.3. CO₂ emissions: N.A. (CV*: N.A.)

4.0.4. Energy consumption: 46 Wh/km (CV*: N.A.)

4.0.5. Electric range: 85 km (CV*: N.A.)

Conversion of the performance of the vehicle:

8.1. Vehicle appropriate for converting its performance level between subcategories (L3e/L4e)-A2 and (L3e/L4e)-A3 and vice versa: yes/no

Additional information:

9.1. Remarks: N.A.

9.2. Exemptions: N.A.