

Golden Lion (Singapore) Holdings Pte. Ltd.  
55 Raffles Place, 34-04#, Land Tower,  
Singapore

## EU CERTIFICATE OF CONFORMITY

The undersigned:  
Ms. Yu Yanping/General Manager  
Hereby certifies that the following complete vehicle:

0.1.	Make:	SAKURA
0.2.	Type:	JS2B
0.2.1.	Variant:	2
0.2.2.	Version:	1
0.2.3.	Commercial name(s) (where appropriate):	JS2B-2
0.3.	Category, subcategory and sub-subcategory of vehicle:	L1e-B
0.4.	Name and address of the manufacturer:	Golden Lion (Singapore) Holdings Pte. Ltd. 55 Raffles Place, 34-04#, Land Tower, Singapore
0.4.2.	Name and address of manufacturer's authorized representative:	Fauro Motor Company S.L. Calle Brasi 24, Tablero De Maspalomas, 35109 Las Palmas, Spain
0.5.1.	Location of the manufacturer's statutory plate(s)	R, x810, y160, z220
0.5.2.	Method of attachment of the manufacturer's statutory plate(s):	Be riveted on the right side of the chassis
0.6.	Location of the Vehicle identification number:	R, x300, y4, z690(t/o)
1.	Vehicle identification number:	PF2EV3F76LC

Conforms in all respects to the type described in EU type-approval e13\*168/2013\*00572\*01 issued on ( 05 11,2020 ) and can be permanently registered in Member States having, having right/left -hand traffic and using metric/imperial units for the speedometer

Place Singapore Date 09 13,2020

signature



# Golden Lion (Singapore) Holdings Pte. Ltd.

55 Raffles Place, 34-04#, Land Tower,  
Singapore

## VEHICLE CATEGORY L

### General construction characteristics

- 1.3 Number of axles: 2 and wheels: 2  
1.3.1 Axles with twinned wheels: n.a. L.3.2 Powered axles: R  
6.2.4 Advanced braking system: None

### Main dimensions

- 2.2.1 Length: 1902 mm 2.2.2 Width: 680 mm 2.2.3 Height: 1140 mm  
2.2.4 Wheel base: 1325mm 2.2.4.1 Wheelbase sidecar: n.a.  
2.2.5 Track width  
2.2.5.1 Track width front: n.a. 2.2.5.2 Track width rear: n.a.  
2.2.5.3 Track with sidecar: n.a. 2.2.10.6 Ground clearance between the axles: n.a.  
2.2.15 Wheelbase to ground clearance ratio: n.a. 2.2.17 Seat height: n.a.  
2.1.1 Mass in running order: 84 kg 2.1.2 Actual mass: 172 kg  
2.1.3 Technically permissible maximum laden mass: 247 kg  
2.1.3.1 Technically permissible maximum on front axle: 75kg  
2.1.3.2 Technically permissible maximum on rear axle: 172kg  
2.1.3.3 Technically permissible maximum mass on sidecar axle: n.a.  
2.1.7 Technically permissible maximum towable mass: Braked: n.a.; Unbraked: n.a.  
2.1.7.1 Technically permissible maximum laden mass of the combination: n.a.  
2.1.7.2 Technically permissible maximum mass at the coupling point: n.a.

### Powertrain

- 3.1.1.1.1 manufacturer: n.a.  
3.1.1.2 Engine code: n.a.  
3.2.1.2 Working principle of the combustion engine: ~~internal combustion engine (ICE)/positive ignition/compression ignition/external combustion engine (ECE)/turbine/compressed air~~  
3.2.1.4.1 Number of cylinders: ---  
3.2.1.4.2 Arrangement of cylinders: ---  
3.2.1.5 Engine capacity: --- cm<sup>3</sup>  
1.9 Maximum net power: n.a.  
1.10 Ratio: maximum net power / mass of the vehicle in running order: --- (kW/kg)  
3.2.3.1 Fuel type: ---  
3.2.3.2 Vehicle Fuel combination: ~~mono-fuel/bi-fuel/flex-fuel~~  
3.2.3.2.1 Maximum amount of bio-fuel acceptable in fuel: n.a.  
3.1.2.1 Manufacturer: Taizhou Quanshun Motor Co.,Ltd  
3.1.2.2 Electric motor code: F3000W  
3.3.3.4  $\pm 5/30^{(1)}$  minutes power: 3.0 kW  
3.1.3.1 Manufacturer: n.a.  
3.1.3.2 Application code: n.a.  
3.3.1 Electric vehicle configuration: pure electric/~~hybrid electric/manpower-electric~~  
3.3.5.2 Category of hybrid electric vehicle: ~~off-vehicle charging/not off-vehicle charging~~  
3.9.2 Maximum assistance factor: n.a.

### Maximum speed

- 1.8 Maximum speed: 45 km/h  
3.9.3 Maximum vehicle speed for which the electric motor gives assistance: n.a.

### Drive-train and control

- 3.5.3.9 Transmission (type): n.a.  
3.5.4 Gear ratios: n.a.  
3.5.4.1 Final drive ratio: n.a.  
3.5.4.2 Overall gear ratio in highest gear: n.a.

### Installation of tyres

- 6.18.1.1 Tyre size designation: Axle 1: 120/70-12 51K 175kpa MT2.75×12  
Axle 2: 120/70-12 51K 225kpa J 3.5×12  
Sidecar wheel: n.a.

### Bodywork

- 6.20.2.1 Door configuration and number of doors: not applicable  
6.16.1 Number of seating positions: 2  
6.16.1.1 Location and arrangement: n.a.

### Coupling devices

- 7.2.8 Type-approval number of coupling device: not applicable

### Environmental performance

- 4.0.1 Environmental step: EURO V  
4.0.6 Sound level measured according to: EU no 134/2014  
4.0.6.1 Stationary: --- dB(A) at engine speed: --- min<sup>-1</sup>  
4.0.6.2 Drive-by: -- dB(A)  
4.0.6.3 Limit value for Lurban: -- dB(A)  
3.2.15 Exhaust emissions measured according to: EU no 134/2014 as amended by 2018/295  
3.2.15.1 Type I test: tailpipe emissions after cold start, including the deterioration factor, if applicable  
CO: --- mg/km THC: --- mg/km NMHC: --- mg/km  
NO<sub>x</sub>: --- mg/km HC+ NO<sub>x</sub>: --- mg/km PM: --- mg/km  
3.2.15.2 Type II test: tailpipe emissions at (increased) idle and free acceleration  
HC: --- ppm at normal idling speed and: --- ppm at high idle speed  
CO: ---% vol. at normal idling speed and: --- % vol. at high idle speed  
3.2.15.3 Smoke corrected absorption coefficient: --- m<sup>-1</sup>

### Energy efficiency

- 4.0.2 Fuel consumption: --- l/kg/100km 4.0.3 CO<sub>2</sub> emissions: --- g/km  
4.0.4 Energy consumption: 18 Wh/km 4.0.5 Electric range: 48 km

### Conversion of the performance of the vehicle

- 8.1 Vehicle appropriate for converting its performance level between subcategories (L3e/L4e)-A2 and (L3e/L4e)-A3 and vice versa: yes/no

### Additional information

- 9.1 Remarks: ---  
9.2 Exemptions: ---