

# COMPLETE VEHICLE EU CERTIFICATE OF CONFORMITY

The undersigned, Mr. Zhang Zhe / Director  
Hereby certifies that the following complete vehicle:

0.1.	Make (trade name of the manufacturer):	Taihong
0.2.	Type: CL-30ZR-60	(CV * Type): N.A.
0.2.1.	Variant: 00	(CV * Variant): N.A.
0.2.2.	Version: 02	(CV * Version): N.A.
0.2.3.	Commercial name (if available): CL-30ZR-60	(CV * Commercial name (if available)): N.A.
0.3.	Category, subcategory and sub-subcategory of vehicle: L6c-A	(CV * Category, subcategory and sub-subcategory of vehicle): N.A.
0.4.	Company name and address of manufacturer:	TAIHONG TECHNOLOGY LIMITED Unit 3, 6/f., kam hon industrial building, 8 wang kwun road, kowloon bay, Hong kong, China
0.4.2.	Name and address of manufacturer's authorized representative (if any):	GREENKAR AUTOMOTIVE SRL ROMA (RM) VIA DI QUARTO PEPERINO 22 CAP 00188 INTERNO 18 ITALY
0.5.1.	Location of the manufacturer's statutory plate(s):	R, x820, y200, z130
0.5.2.	Method of attachment of the manufacturer's statutory plate(s):	By riveted on the chassis
0.6.	Location of the vehicle identification number:	R, x300, y5, z240
1.	Vehicle identification number:	☆R26300029R1027399☆

General construction characteristics	
1.3.	Number of axles: 2 and wheels: 4
1.3.1.	Axles with twinned wheels: N.A.
1.3.2.	Powered axles: R
6.2.4.	Advanced braking system: ABS / CBS / Both ABS and CBS / None:

Main dimensions	
2.2.1.	Length: 1520 mm
2.2.2.	Width: 670 mm
2.2.3.	Height: 1000 mm
2.2.4.	Wheelbase: 1030 mm
2.2.4.1.	Wheelbase sidecar: N.A.
2.2.5.	Track width
2.2.5.1.	Track width front: 490 mm
2.2.5.2.	Track width rear: 580 mm
2.2.5.3.	Track width sidecar: N.A.
2.2.10.6	Ground clearance between the axles: N.A.
2.2.15.	Wheelbase to ground clearance ratio: N.A.
2.2.17.	Seat height: N.A.

Masses	
2.1.1.	Mass in running order: 88 kg
2.1.2.	Actual mass: 195 kg
2.1.3.	Technically permissible maximum laden mass: 215 kg
2.1.3.1.	Technically permissible maximum mass on front axle: 70 kg
2.1.3.2.	Technically permissible maximum mass on rear axle: 145 kg
2.1.3.3.	Technically permissible maximum mass on sidecar axle: N.A.
2.1.7.	Technically permissible maximum towable mass:
	Braked: N.A. Unbraked: N.A.
2.1.7.1.	Technically permissible maximum laden mass of the combination: N.A.
2.1.7.2.	Technically permissible maximum mass at the coupling point: N.A.

Conforms in all respects to the type described in EU type-approval e9\*168/2013\*H215\*06 (type-approval number including extension number) (CV\* type-approval number including extension number) issued on 05.09.2023 (date of issue) (CV\* date of issue) and

can be permanently registered in Member States having right/left-hand traffic and using metric/imperial units for the speedometer.

HONG KONG, China (place) 2024. 01. 18 (date)

  
\_\_\_\_\_  
(signature)

Powertrain	
3.1.1.1.	Manufacturer: N.A.
3.1.1.2.	Engine code (as marked on the engine or other means of identification): N.A.
3.2.1.2.	Working principle of the combustion engine: internal combustion engine (ICE)/ignition/compression ignition/external combustion engine (ECE)/turbine/positive compressed air
3.2.1.4.1.	Number of cylinders: N.A.
3.2.1.4.2.	Arrangement of cylinders: LI/V/O/S
3.2.1.5.	Engine capacity: N.A.
1.9.	Maximum net power: N.A. (CV*: N.A.)
1.10.	Ratio maximum net power/mass of the vehicle in running order: N.A. (CV*: N.A.)
3.2.3.1.	Fuel type: N.A.
3.2.3.2.	Vehicle fuel combination: mono-fuel/bi-fuel/flex-fuel
3.2.3.2.1.	Maximum amount of bio-fuel acceptable in fuel: N.A.



3.1.2.1.	Manufacturer: Taizhou Zhongdong Technology Co., Ltd.		Environmental performance	
3.1.2.2.	Electric motor code (as marked on the engine or other means of identification):  2D60V1000#20240101410		4.0.1.	Environmental step: Euro 5 (3/4/5/5+) <sup>(1)</sup>
3.3.3.4.	15/30 minutes power:	1.0 kW	4.0.6.	Sound level measured according to: N.A.
3.1.3.1.	Manufacturer:	N.A.	4.0.6.1.	Stationary: N.A. (CV*: N.A.)
3.1.3.2.	Application code (as marked on the engine or other means of identification): N.A.		4.0.6.2.	Drive-by: N.A. (CV*: N.A.)
3.3.1.	Electric vehicle configuration: <del>pure electric/hybrid electric/manpower</del> electric		4.0.6.3.	Limit value for L <sub>urban</sub> : N.A. (CV*: N.A.)
3.3.5.2.	Category of hybrid electric vehicle: <del>off-vehicle charging/not off-vehicle charging</del>		3.2.15.	Exhaust emissions measured according to N.A.
3.9.2.	Maximum assistance factor:	N.A.	3.2.15.1.	Type I test: tailpipe emissions after cold start, including the deterioration factor, if applicable: CO : N.A. (CV*: N.A.) THC : N.A. (CV*: N.A.) NMHC : N.A. (CV*: N.A.) NOx : N.A. (CV*: N.A.) THC+NOx : N.A. (CV*: N.A.) PM : N.A. (CV*: N.A.)
Maximum speed			3.2.15.2.	Type II test: tailpipe emissions at (increased) idle and free acceleration: HC: N.A. ppm at normal idling speed and: N.A. ppm at high idle speed (CV*: N.A.) CO: N.A. %vol at normal idling speed and: N.A. %vol at high idle speed (CV*: N.A.)
1.8.	Maximum speed of vehicle: 25 km/h (CV*: N.A.)		3.2.15.3.	Smoke corrected absorption coefficient : N.A. (CV*: N.A.)
3.9.3.	Maximum vehicle speed for which the electric motor gives assistance: N.A.		Energy efficiency	
Drive-train and control			4.0.2.	Fuel consumption: N.A. (CV*: N.A.)
3.5.3.9.	Transmission (type): A		4.0.3.	CO <sub>2</sub> emissions: N.A. (CV*: N.A.)
3.5.4.	Gear ratios: 13.176		4.0.4.	Energy consumption: 69 Wh/km (CV*: N.A.)
3.5.4.1.	Final drive ratio: N.A.		4.0.5.	Electric range: 43 km (CV*: N.A.)
3.5.4.2.	Overall gear ratio in highest gear: N.A.		Conversion of the performance of the vehicle:	
Installation of tyres			8.1.	Vehicle appropriate for converting its performance level between subcategories (L3e/L4e)-A2 and (L3e/L4e)-A3 and vice versa: yes/no
6.18.1.1.	Tyre size designation: Axle 1: 3.00-8 (38J) Minimum Load capacity index: Axle 1: 16	Axle 2: 3.00-10 (42J)  Axle 2: 17	Additional information:	
	Minimum speed category symbol: Axle 1: B Recommended pressure: Axle 1: 225 kpa	Axle 2: B  Axle 2: 225 kpa	9.1.	Remarks: N.A.
	Rim size: Axle 1: MT 1.75x8 Sidecar wheel: N.A.	Axle 2: MT 2.15x10	9.2.	Exemptions: N.A.
Bodywork				
6.20.2.1.	Door configuration and number of doors: N.A.			
6.16.1.	Number of seating positions: 1			
6.16.1.1.	Location and arrangement: rl:1C			
Coupling devices				
7.2.8.	Type-approval number of coupling-device: N.A.			