

# COMPLETE VEHICLE EU CERTIFICATE OF CONFORMITY

The undersigned, Gong Liang, sales manager  
Hereby certifies that the following complete vehicle:

- 1.1. Make (trade name of the manufacturer): SLANE
- 1.2. Type: T-01
- 1.2.1. Variant: 0
- 1.2.2. Version: 0
- 1.2.3. Commercial name (if available): LDR-35
- 1.3. Category, subcategory and sub-subcategory of vehicle: L2e-U
- 0.4. Company name and address of manufacturer:  
Slane Vehicle Co., Ltd.(Wuxi)  
Zone A, Yangjian Mechanical Manufacturing Park, Xishan District, Wuxi City, Jiangsu Province, China
- 0.4.2. Name and address of manufacturer's authorized representative (if any):  
ELETTRONICA TIRRITO S.R.L  
VIA SAN LEONE 169 ENNA(EN) CAP 94100, ITALY
- 1.5.1. Location of the manufacturer's statutory plate(s): L, x800, y340, z280
- 1.5.2. Method of attachment of the manufacturer's statutory plate(s): Riveted
- 0.6. Location of the vehicle identification number: R, x260, y25, z760
1. Vehicle identification number: LW5EWF107P1001889  
conforms in all respects to the type described in EU type-approval (e13\*168/2013\*00862\*00 type-approval number including extension number) issued on (20, 05, 2020 date of issue)  
and can be permanently registered in Member States having right/left-hand traffic and using metric/imperial units for the speedometer.

Wuxi, China

28, 09, 2022

(place)

(date)

(signature)

## General construction characteristics

- 1.3. Number of axles: 2 and wheels: 3
- 1.3.1. Axles with twinned wheels: N.A.
- 1.3.2. Powered axles: R
- 6.2.4. Advanced braking system: ABS / CBS / Both ABS and CBS / None

## Main dimensions

- 2.2.1. Length: 3010 mm
- 2.2.2. Width: 1020 mm
- 2.2.3. Height: 1400 mm
- 2.2.4. Wheelbase: 2020 mm
- 2.2.4.1. Wheelbase sidecar: N.A.
- 2.2.5. Track width
- 2.2.5.1. Track width front: N.A.
- 2.2.5.2. Track width rear: 900 mm
- 2.2.5.3. Track width sidecar: N.A.
- 2.2.10.6 Ground clearance between the axles: N.A.
- 2.2.15. Wheelbase to ground clearance ratio: N.A.
- 2.2.17. Seat height: N.A.

## Masses

- 2.1.1. Mass in running order: 200 kg
- 2.1.2. Actual mass: 356 kg
- 2.1.3. Technically permissible maximum laden mass: 542 kg
- 2.1.3.1. Technically permissible maximum mass on front axle: 170 kg
- 2.1.3.2. Technically permissible maximum mass on rear axle: 372 kg
- 2.1.3.3. Technically permissible maximum mass on sidecar axle: N.A.
- 2.1.7. Technically permissible maximum towable mass:  
Braked: N.A. Unbraked: N.A.
- 2.1.7.1. Technically permissible maximum laden mass of the combination: N.A.
- 2.1.7.2. Technically permissible maximum mass at the coupling point: N.A.

## Powertrain

- 3.1.1.1. Manufacturer: N.A.
- 3.1.1.2. Engine code (as marked on the engine or other means of identification): N.A.
- 3.2.1.2. Working principle of the combustion engine: internal combustion engine (ICE)/positive ignition/  
compression ignition/external combustion engine (ECE)/turbine/compressed air N.A.
- 3.2.1.4.1. Number of cylinders: N.A.
- 3.2.1.4.2. Arrangement of cylinders: H/V/O/S N.A.
- 3.2.1.5. Engine capacity: N.A.
- 1.9. Maximum net power: N.A.
- 1.10. Ratio maximum net power/mass of the vehicle in running order: N.A.
- 3.2.3.1. Fuel type: N.A.
- 3.2.3.2. Vehicle fuel combination: mono-fuel/bi-fuel/tri-fuel N.A.
- 3.2.3.2.1. Maximum amount of bio-fuel acceptable in fuel: N.A.
- 3.1.2.1. Manufacturer: Xuzhou Nanpu Electromechanical Technology Co., Ltd.
- 3.1.2.2. Electric motor code (as marked on the engine or other means of identification):  
72V1200W2307W04C1065



3.3.3.4. 45/30 minutes power: 1.2 kW at 2940 min<sup>-1</sup>  
 3.1.3.1. Manufacturer: N.A.  
 3.1.3.2. Application code (as marked on the engine or other means of identification): N.A.  
 3.3.1. Electric vehicle configuration: pure electric/hybrid electric/manpower-electric  
 3.3.5.2. Category of hybrid electric vehicle: off-vehicle charging/not off-vehicle charging N.A.  
 3.9.2. Maximum assistance factor: N.A.

#### Maximum speed

1.8. Maximum speed of vehicle: 35 km/h  
 3.9.3. Maximum vehicle speed for which the electric motor gives assistance: N.A.

#### Drive-train and control

3.5.3.9. Transmission (type): O.  
 3.5.4. Gear ratios: Forward gear: 10.0, Reverse gear: 10.0  
 3.5.4.1. Final drive ratio: N.A.  
 3.5.4.2. Overall gear ratio in highest gear: N.A.

#### Installation of tyres

6.18.1.1. Tyre size designation:  
 Axle 1:  
 Option 1: 3.00-12 47J 2.10x12 250 kPa  
 Option 2: 3.75-12 66J 2.50x12 250 kPa  
 Axle 2:  
 Option 1: 4.00-12 65J 2.50x12 250 kPa  
 Option 2: 4.00-12 72J 2.50x12 250 kPa  
 Option 3: 4.00-12 70J 2.50x12 250 kPa  
 Option 4: 80/100-12 55J 1.85x12 250 kPa  
 Sidecar wheel: N.A.

#### Bodywork

6.20.2.1. Door configuration and number of doors: N.A.  
 6.16.1. Number of seating positions: 1  
 6.16.1.1. Location and arrangement: r1: 1C

#### Coupling devices

7.2.8. Type-approval number of coupling device: N.A.

#### Environmental performance

4.0.1. Environmental step: Euro (3/4/5/5+).  
 4.1.6. Sound level measured according to: N.A.  
 4.1.6.1. Stationary: N.A. at engine speed: N.A.  
 4.1.6.2. Drive-by: N.A.  
 4.1.6.3. Limit value for L<sub>urban</sub>: N.A.

3.2.15. Exhaust emissions measured according to Regulation (EU) No 134/2014 including all amendments up to (EU) 2018/295  
 3.2.15.1. Type I test: tailpipe emissions after cold start, including the deterioration factor, if applicable:  
 CO: N.A.  
 THC: N.A.  
 NMHC: N.A.  
 NOx: N.A.  
 THC+NOx: N.A.  
 PM: N.A.

3.2.15.2. Type II test: tailpipe emissions at (increased) idle and free acceleration:  
 HC: N.A.  
 CO: N.A.

3.2.15.3. Smoke corrected absorption coefficient: N.A.

#### Energy efficiency

4.1.2. Fuel consumption: N.A.  
 4.1.3. CO<sub>2</sub> emissions: N.A.  
 4.1.4. Energy consumption: 73 Wh/km  
 4.1.5. Electric range: 74 km

#### Conversion of the performance of the vehicle:

8.1. Vehicle appropriate for converting its performance level between subcategories (L3e/L4e)-A2 and (L3e/L4e)-A3 and vice versa: yes/no N.A.

#### Additional information:

9.1. Remarks: N.A.  
 9.2. Exemptions: N.A.